

Construction specs

(Barns)

Floors

- **Runners** - 4"x6" Pressure Treated Runners with 1-1/2" x 1-1/2" dado notch for floor joist.
- **Perimeter Rails** - 2" x 4" Pressure Treated
- **Floor Joists** - 2"x 4" Pressure Treated 16" OC
- **Fasteners** - All joist connected to runner with #8 x 3" screw, quantity of 4 per joist. 2- 4" lag bolts every 4 ' runner to joist connection
- Decking - 5/8" T&G Treated Plywood
- Decking Fasteners - Hot-dipped Galvanized ring shank nails

Walls

- Top/Bottom Plates - 2"x 4" #1 SYP
- 2" x 4" #1 SYP studs 24" OC with Double Studs under Siding Seams

Exterior Siding

- Treated 5/8" T-111 Plywood stained with Cedar Bark
- Hot-dipped Galvanized ring shank nails

Roof Framing

- 2" x 4" #1 SYP 2' OC

Roof

- 29 gauge Galvalume Steel Roof (Red, Green, Black, Burnished Slate)
- Optional Residential Architectural Shingles (Black and Weathered Wood)
- Steel Roof Fasteners - #10 x 1" Fasteners with Control Seal Washers

Doors and Windows

- 8' Wide Buildings come with a Single Wooden Door
- 10' and 12' Wide Buildings come with a Double Wooden Door
- All buildings come with locks and keys.
- 24" x 36" and 36" x 36" Bronze Windows- optional